

~~SECRET~~ CONFIDENTIAL

25X1

JUN 22 1956

Registered-Return Receipt Requested

25X1

Attention:

President

Subject : (Change Order No. 1  
Task Order No. 1  
Contract No. RD-122

DOC	27	REV DATE	19 MAR 1980	BY	064540
ORIG COMP	035	OPI	56	TYPE	06
ORIG CLASS	035	PAGES	2	REV CLASS	C
JUST	22	NEXT REV	2010	AUTH:	HR 70-2

25X1

ILLEGIB

Gentlemen:

Reference is made to Task Order No. 1 dated 28 June 1956.

This Change Order authorizes the amendments as listed on the attachment entitled "Amendment No. 1 - Specification No. 56-A-1046-A" which is made a part hereof.

All other terms and conditions of the Task Order shall remain the same and in full force and effect.

Please indicate your acceptance of the foregoing by signing this letter and the enclosed three copies thereof. Retain one copy for your records and return the signed original and remaining two copies to the undersigned at the earliest practicable date.

Very truly yours,

/s/

Contracting Officer

25X1

ACKNOWLEDGED AND ACCEPTED THIS

28 DAY OF Aug 1956

AGENCY STERILE

25X1

TITLE

Pres

## NOTICE

This material contains information of the national defense of the United States. The unauthorized disclosure of this information, or the transmission or revelation of which in any manner to an unauthorized person is prohibited by law.

Issued in accordance with memo from Chf, ED/OC dtd 31 July 56 to Chf, PD/OL

~~SECRET~~ CONFIDENTIAL

~~SECRET~~

AMENDMENT NO. 1 - SPECIFICATION NO. 56-A-1046-A

3.3.1. Crystal Control

Delete existing paragraph and substitute:

The frequency of emission shall be determined by means of a crystal controlled oscillator and using crystals whose fundamental frequency ranges from 3 megacycles to 10 megacycles. Crystal control shall be accomplished by utilizing the Armed Services crystal unit, CR-18/U in the HC-6/U holder.

3.3.1.1. Oscillator Circuitry

Delete existing paragraph and substitute:

The crystal circuit shall be designed to operate in the parallel mode. The crystal load capacity shall be 32 micromicrofarads plus or minus one-half micromicrofarad, and the crystal drive power shall not exceed ten (10) milliwatts. The oscillator shall exhibit no evidence of crystal over-mode oscillation, and shall show no evidence of oscillation with the crystal removed, under any condition of transmitter tuning or loading.

5.3. Dimensions

Line 3 - Delete: "receiver is 6 5/8" etc."

Substitute: "receiver is 7" etc."

TEST SPECIFICATION NO. 56-A-1046-A-T

3.3.1. Paragraph d., Line 3 - Insert "50" after "of the meter:"

CONFIDENTIAL

~~SECRET~~